



ORION TELECOM NETWORKS INC.

TM

T1-GSM

**T1 Channel Bank with
24 X GSM Interface(s)
72 SIMs per T1 Interfaces**

- **Product Overview**
- **Features & Highlights**
- **Ordering Information**
- **Product Specifications**
 1. **T1 Interface**
 2. **GSM Interface**

16810, Avenue of Fountains, Suite # 108,
Fountain Hills, AZ 85268, USA

Phone: +1 (480) 8168672

Fax: +1 (480) 8160115

E-mail: sales@oriontelecom.com

Web Site: <http://www.oriontelecom.com>

Product Overview:

Orion introduces the latest T1 GSM Gateway with 72 SIMs (3 SIMs per each GSM channel - 72 SIMs per T1). Each GSM channel individual programmable to work with any of the 3 SIMs assigned to that GSM channel according to the "user" programmed time-table ("user" programmed time-of-day schedule). This enables the user to program a least-cost operation so that traffic, at any time-of-day, is only directed to the preferred SIM (out of the 3 SIM cards per GSM channel) - which shall activate only according to the "user" programmed time-table ("user" programmed time-of-day schedule). The latest compact T1 GSM Gateway solution integrates the T1 interface to the GSM network to provide the user with 72, GSM links (72 SIMs) for mobile communications with an integrated T1 interface.

The T1 GSM Gateway / T1 GSM Channel Bank offers numerous applications for operators, which include terminating VoIP, VoATM, VoFR, VPN, DCME E1 / T1 traffic directly into the GSM network, connecting remote (distant) locations over GSM networks, providing rural connectivity over GSM networks, last mile connectivity over GSM networks, quick basic telephony provisioning, corporate business fixed to mobile / mobile to fixed, GSM connectivity for river boats, costal cruise ships, fixed network back-up via GSM, VPN connectivity between two corporate networks, mobile back-up solutions for corporate businesses with high security requirements, and many more applications.

The T1 GSM gateway also replaces the cumbersome fixed wireless terminals and provides accurate answer supervision and line disconnect supervision, plus a host of other advantages, which include fast connection times (very short PDD) and high ASR rates that compete with the industry's best.

Orion offers both E1 GSM Gateways and T1 GSM gateways / GSM channel banks with the following features:

- The interface of the network side is T1 Digital Interface.
- The interface on the user side is up to 24 x GSM links (72 SIMs per T1 - 3 SIM per channel).
- Accurate answer supervision and disconnect supervision.
- Each GSM channel individual programmable to work with any of the 3 SIMs, according to the user programmed time-of-day schedule. This enables the user to program a least-cost operation so that traffic of each GSM channel is directed to the preferred SIM (out of the 3 SIM cards per channel) - which shall be activated only according to the "user" programmed time-table ("user" programmed time-of-day schedule).
- GSM Gateway to automatically "call" a "user" programmed number at a "user" programmed time-of-day, once every 24 hours to confirm to the operator that each GSM channel is in operation.

- Pre-Paid Balance Enquiry: GSM Gateway automatically enquire each PRE-PAID GSM SIM card for balance minutes / balance credits and sending an SMS message with this information to a "user" programmed number at a "user" programmed time-of-day.
- Mix 'n' Match 3 SIM per channel and 1 SIM per channel GSM access cards.
- Unique caller ID blocking feature (if network allows)
- Echo cancellation up to 128ms. provided - optional
- Remote access monitoring over TCP/IP network - optional
- Unique out-bound calling, user programmable, access feature.
- All 24, GSM channels are dual band - 900MHz and 1800MHz with auto-sense / auto-switching capability.
- All 24, GSM channels are dual band - 900MHz and 1900MHz with auto-sense / auto-switching capability.

Features and Highlights

- Compact, 24 GSM terminals (72 SIMs per T1) in a 19-inch chassis.
- GSM is integrated to the T1 Interface.
- Exceptional voice quality. The two wire trans-hybrid analog path (present in the Fixed Wireless Terminals) is eliminated in the innovative design, resulting in improved voice quality, clearer voice and superior channel separation by reducing the susceptibility to echoes that result from the analog two wire trans-hybrid VF paths.
- Provides accurate billing information ("answer supervision" and "line disconnect supervision") - not provided by Fixed Wireless Terminals.
- Integrated, optional, T1 Echo-Canceller to cancel echo tails from inherent delays of VoIP / VoFR networks - 64ms. uni-directional, 128ms. uni-directional and 64ms. bi-directional options available.
- Lower cost - resulting from complete, GSM to T1 integration.
- Plug-And-Play. Easy to install. Takes only minutes to install and start service.

Orion's Integrated E1 / T1 GSM Channel Bank - PROS

Third Party, component solutions comprising of E1 / T1 Channel Banks and 24 (T1) / 30 (E1) Fixed Wireless Terminals - CONS

<p>1. Integrated and Compact. 24 (T1), or 30, (E1) GSM channels in a compact 6U high, 19-inch rack-mountable shelf.</p>	<p>1. Discreet and poorly managed solution comprising of a channel bank and discreet and 24 (T1) / 30 (E1) Fixed Wireless Terminals.</p>
<p>2. Integrated, Single Power Input: -48VDC or AC Mains. Both options are provided.</p>	<p>2. Individual, 24 (T1) / 30 (E1) Fixed Wireless Terminals with 30, separate power inputs. Difficult to manage.</p>
<p>3. 3.5dB gain, external antennas with 2 meter Rg174 cable and antenna trays. Easy to manage.</p>	<p>3. Absence of External Antennas provides no additional signal gain.</p>
<p>4. Offers Remote and Integrated Graphical User Interface (GUI) Management to monitor all GSM channels. This option allows the USER to view and monitor the status of ALL 24 / 30 GSM channels, including FAULTS on any of the individual GSM channels, remotely, over a TCP-IP network.</p>	<p>4. No management facility to monitor the GSM terminals remotely, or to view the channel or fault status on any of the GSM channels.</p>
<p>5. Integrated, 64ms. and 128ms. Echo-Canceller option. This option allows the USER to install a 64ms. / 128ms. Echo Canceller in the same 19-inch chassis, to effectively remove any echoes resulting From VoIP and VoFR network delays.</p>	<p>5. No option of ANY Echo-Canceller, which are often essential and required in VoIP and VoFR call termination, owing to unacceptable echoes which often result from network delays.</p>
<p>6. Direct E1 - A Law to GSM Conversion, or, Direct T1 Mu Law to GSM conversion, with patented (patent pending) noise reduction technology. Greatly improves voice quality and voice clarity.</p>	<p>6. Poor coupling of analog lines (from the E1/ T1 channel banks) to GSM Fixed Wireless Terminals often results in the analog lines picking up a lot of GSM transmission noise often resulting in unacceptable voice quality and poor quality service.</p>
<p>7. Greater product reliability. Integration results in greater product reliability and results in less downtime resulting from a low failure rate.</p>	<p>7. Poor product reliability resulting from low integration, poor management and a high number of individual components that are required to be managed (24 or 30 individuals Fixed Wireless Terminals, each with separate power supplies, and the channel bank.</p>

Orion's Integrated E1 / T1 GSM Channel Bank - PROS

Third Party, component solutions comprising of E1 / T1 Channel Banks and 24 (T1) / 30 (E1) Fixed Wireless Terminals - CONS

<p>8. Unique dial-out,user programmable access. USER PROGRAMMABLE, call directory interface. This optional feature, unique to E1 / T1, GSM Multiplexer, allows the USER to program "out-bound" calls (GSM Network to E1 / T1), to be restricted to a list of USER pre-programmed numbers only. This feature can be used to provide limited access to out-going calls (GSM Network to E1 / T1), on dedicated channels, which the service provider may wish to RESERVE only for its SUBSCRIPTION CUSTOMERS wishing to use out-bound long-distance services (GSM Network to E1 / T1), through VoIP / VoATM networks.</p> <p>This option also allows the USER to RESTRICT, or to ALLOW all calls originating from the GSM Network to E1 / T1 VoIP / VoATM Gateway.</p>	<p>8. No USER PROGRAMMABILITY to RESTRICT or ALLOW calls based a USER PROGRAMMABLE directory. No such feature is provided, or offered in the Fixed Wireless Terminal Channel Bank solution.</p>
<p>9. Accurate CALL METERING resulting from accurate answer-supervision and line-disconnect supervision since the integrated E1 / T1, GSM Channel Bank derives its answer-supervision (required for the call-metering function), from the SS7 based GSM Network Signaling / GSM Switch.</p>	<p>9. Unreliable CALL METERING resulting from a battery reversal based, or VAD based (Voice Activated) answer supervision, which is based on analog technology and prone to errors. A VAD based answer supervision offers unreliable CALL METERING, in comparison with the integrated E1 / T1, GSM Channel Bank which derives its answer-supervision (required for the call-metering function), from the SS7 based GSM Network Signaling / GSM Switch.</p>
<p>10. Low Cost. Integration also results in cost reduction when compared with a component based, discreet solution comprising of a T1 / E1 channel bank PLUS 24 / 30 Fixed Wireless Terminals.</p>	<p>10 Higher cost. The cost appears to be even higher, the absence of any available features, and if poor product management, poor product integration resulting in lower product reliability is taken into consideration.</p>

Technical Specifications

T1 Interface Card

Number of T1 Interfaces	One Number of GSM Channels = 24 Number of SIMs per each GSM Channel = 3 Total Number of SIMs per T1 = 72
Conformity	G.703
Framing	D4
Signaling	D4, Robbed-Bit , E&M Wink-Start Signaling with answer supervision
PCM Sampling Rate	8000 samples / second.
Encoding Law	Mu Law
Bit Rate	1544Kbps 50ppm.
Code	AMI, B8ZS - Selectable
Nominal Impedance	100 Ohms Standard (75 Ohms Optional)
Connector	RJ45 (100 Ohms Impedance)
Peak Voltage of a mark For 100 Ohms Balanced Interface	3.0 Volt 0.3 Volt.
Pulse Mask	As per ITU-T (CCITT) Rec. G.703
Output Jitter	<0.05UI (in the frequency range of 20Hz to 100KHz).
Permissible Attenuation	6dB at 1MHz
Return Loss at:	
51.2 KHz to 102.4 KHz.	> 12dB
102.4 KHz to 2048 KHz	> 18dB
2048 KHz to 3072 KHz	> 14dB
Jitter Tolerance	As per ITU-T (CCITT) G.823
Loss and Recovery of Frame Alignment	As per Clause 3 of ITU-T (CCITT) G.732
Loss and Recovery of Multi-Frame Alignment	As per Clause 5.2 of ITU-T (CCITT) G.732

Power Supply Card

Input DC voltage	- 48V DC (nominal)
Range of input	- 40V to -60V DC
Output voltages	+5V
Full Load Output Current	18A@5VDC
Input Voltage Reversal Protection	Provided in the Card
Over Current Protection	20A for +5V
Short Circuit Protection	Current limit - 20A. Recovers on removal of short
Under Voltage	< 4.5V
Over Voltage	5.4V to 5.6V
Efficiency at full load	>80%
Ripple at full load	<5mVrms
Spike at full load	<50mV
Power Consumption	120 Watts (Worst Case)

GSM Access Card

Number of GSM Interfaces	1 ~ 72 (Stackable, 1 thru 72).
Type	Dual Band EGSM 900 MHz and EGSM 1800 MHz.
Compliance	Compliant with ETSI GSM Phase 2+ standard (Normal MS) Class 4 (2W @ 900MHz) Class 1 (1W @ 1800 Mhz)
Approvals	Fully Type Approved to GSM Standards
SIM Interface Internal Tray	Toolkit Class 2. 3V Reader
Voice Features	Full Rate, Enhanced Full Rate And Half-Rate (FR/EFR/HR)
DTMF	Dual Tone Multi FrequencyFunction (DTMF) Dialing Support

Alarms

An alarm shall be displayed in LED L1 / L2 for the following reasons

1. Invalid SIM Card
2. Unregistered SIM Card
3. Faulty SIM Card
4. Faulty GSM Module
5. GSM Access Card Out of Range

Echo Canceller Card

- Provides voice echo cancellation of up to 64ms / 128ms
- Conforms to ITU-T G.165 and ITU-T G.168
- G.164 /G.165 disable tone detection
- Non-Linear Processor with Comfort Noise Insertion
- Narrow-Band Detector
- Eliminates long echo tail.

T1 Echo Canceller - T1 Interface (Optional)

Number of Interfaces	2, 1 - Input 1 - Output
Conformity	G.703
Frame Structure	As per ITU (CCITT) G.704
Signaling	D4, E&M Wink-Start Signaling
PCM Sampling Rate	8000 Samples / sec
Encoding Law	Mu Law as per ITU (CCITT) G.711
Bit Rate	1544 Kbps \pm 50 ppm
Code	HDB3
Nominal Impedance	100 Ω balanced
Peak Voltage of a mark For 100 Ω Balanced interface	3.0 V \pm 0.3 V
Peak Voltage of a space for 100 Ω Balanced interface	0 V \pm 0.3 V
Nominal Pulse Width	244 ns
Pulse Mask	as per ITU (CCITT) Rec. G.703
Output Jitter	< 0.05 UI (in the frequency range of 20Hz to 100 KHz)
Permissible Attenuation	6 dB at 1 MHz
Return Loss at:	
51.2 KHz to 102.4 KHz	> 12dB
102.4 KHz to 2048KHz	> 18dB
2048KHz to 3072 KHz	> 14dB
Jitter Tolerance	As per ITU (CCITT) G.823
Loss and recovery of frame alignment :	As per clause 3 of ITU (CCITT) G.732
Loss and recovery of multiframe alignment :	As per clause 5.2 of ITU (CCITT) G.732

Mechanical Specifications:

Rack Mounting	Standard 19-Inch DIN Rack
Height	6U (265 mm)
Depth	290 mm
Width	19-inch (477mm)
Weight	10.5Kgs. (Net)

Ordering Information

Sr. No.	Part No.	Product Description	Qty
1.	T1-015	Control Card, T1 Interface Card	01
2.	T1-000 / 005	19" Shelf 3U High (Sub-rack) to accommodate 24 GSM Channels with Connectorized Backplane 6U High	01
3.	T1-010	(-) 48VDC Power Supply Card	02
4.	T1-024	Dual Port GSM Interface Card - GSM terminals connect to an T1 interface, 15 Cards (max) per system	12 (max.)
5.	T1-024-ANT	External Antennas with 2 Meter Connectorized cable	24
6.	T1-150W	Power Supply (External) AC to DC Converter Portable External Converter Universal AC Input [93VAC-276VAC, 47Hz-63Hz] to DC Output [(-) 48VDC]	01

Common Equipment

Optional

7.	T1-TCP-IP	TCP-IP remote access for configuration Option allows the user to access, configure and control the T1-GSM / T1 Channel Bank equipment over a TCP-IP network. 1 Required for every T1-GSM Shelf	01
----	-----------	---	----

Technical specification are subject to change without notice.
Windows is the registered Trademark of Microsoft Corporation, USA.
All brand names and trademarks are the property of their respective owners.
Revision 02. 01 September 2005.